



DR Congo power safe opzs

What makes EnerSys powersafe OPzS batteries special?

Dilute sulfuric acid electrolyte with specific gravity of 1.240 Lead alloy leak proof terminal and fully insulated solid copper inter-cell connectors Engineered with an optimized plate design, EnerSys PowerSafe OPzS batteries feature an increased capacity exceeding the DIN standard.

Why should you choose powersafe OPzS batteries?

The pasted negative flat plate design provides the perfect balance for maximum performance. The robust design of PowerSafe OPzS batteries makes them a perfect fit for your application.

What are powersafe OPzS cells used for?

The specification of the PowerSafe OPzS cells make it ideal for a wide range of applications such as telecommunications, power generation and distribution, railway, airport and seaport signalling, computing, emergency lighting, automation and measuring systems.

Are powersafe OPzS batteries ISO 9001 certified?

Batteries must be installed in accordance with IEC 62485-2 and national/local regulations The management systems governing the manufacture of PowerSafe OPzS products are ISO 9001, ISO 14001 and ISO 45001 certified 2022 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted.

The EnerSys range of PowerSafe OPzS batteries has been designed for use in all standby power applications that demand the highest levels of reliability and security. PowerSafe OPzS cells benefit from an optimised plate design that results in increased capacity compared to the requirements of the internationally recognised DIN standard. In

Engineered with an optimized plate design, PowerSafe OPzS batteries feature an increased capacity exceeding the DIN standard. Additionally, the die cast tubular plate design with low antimony offers excellent cycling capabilities and a proven long life under float conditions.

Designed to deliver the highest levels of reliability and security, PowerSafe OPzS batteries are used in wide range of applications, including telecommunications, power generation and distribution, railway, airport and seaport signaling, computing, emergency lighting, and more.

EnerSys PowerSafe OPzS Features. Capacity from 217 to 3543 Ah; 20 year service life at 20 degrees C; 3 year topping interval; Low maintenance; Terminals - lead alloy leak-proof pole with brass insert designed to give minimum resistance and maximum current flow; Fully insulated, solid copper inter-cell connectors allow for voltage measurements

